

Description

diameter: 1/8", grip range: 0.126" - 0.187", nas1097, flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3214-4-3](#)

SKU / Model:	CR3214403
Minimum Qty (MOQ):	100
NSN:	5320-01-581-8326
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3214-4-03 Specifications

Fastener Length:	1.380 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.188 Inches Minimum And 0.196 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Cherry Max Rivet Nominal Diameter Nas 1097 100 Degrees Flush Head (pin-rivet)
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.