

Description

diameter: 1/8", grip range: 0.126" - 0.187", nas1097, flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3214-4-3](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3214403 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-581-8326 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N CR3214-4-03 Specifications

| | |
|--|---|
| Fastener Length: | 1.380 Inches Nominal |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.125 Inches Minimum And 0.129 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.188 Inches Minimum And 0.196 Inches Maximum |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Cherry Max Rivet Nominal Diameter Nas 1097 100 Degrees Flush Head (pin-rivet) |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment: | Cadmium Stem And Chromate Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.