

Description

diameter: 1/8", grip range: 0.251" - 0.312", nas1097, flush head, aluminum sleeve, steel stem, CherryMax, CR3214 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3214-4-5](#)

SKU / Model:	CR3214405
Minimum Qty (MOQ):	100
NSN:	5320-01-300-6840
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3214-4-05 Specifications

Fastener Length:	1.565 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.085 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Minimum Tensile Strength:	345000 Pounds Per Square Inch
Shear Strength:	814 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.