

**Description**

Fastener Length: 1-3/8", CR3214 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3214-4-02](#)

SKU / Model:	CR321442
Minimum Qty (MOQ):	100
NSN:	5320-01-258-6058
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3214-4-2 Specifications

<b>Fastener Length:</b>	1.320 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Head Major Diameter:</b>	0.188 Inches Minimum And 0.196 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	W/s: Aircraft, F-111; Aircraft, Intruder A-6e; Ah-64-d Longbow; Helicopter, Apache Ah-64; Aircraft, Thunderbolt II, A-10; Helicopter, Utility/Search And Recovery Un-1n
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.