

Description

diameter: 5/32", grip range: 0.126" - 0.187", flush head, aluminum sleeve, steel stem, CR3214 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3214-5-3](#)

SKU / Model:	CR3214503
Minimum Qty (MOQ):	100
NSN:	5320-01-385-5438
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR3214-5-03 Specifications

Fastener Length:	0.290 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.158 Inches Nominal
Head Major Diameter:	0.232 Inches Nominal
Expansion Device:	Threaded Stem
Grip Length:	0.250 Inches Nominal
Countersink Angle:	125.0 Degrees Nominal
Material:	Aluminum Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.