

**Description**

diameter: 5/32", grip range: 0.126" - 0.187", flush head, aluminum sleeve, steel stem, CR3214 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3214-5-3](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3214503                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5320-01-385-5438                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



## P/N CR3214-5-03 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.290 Inches Nominal   |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.158 Inches Nominal   |
| <b>Head Major Diameter:</b> | 0.232 Inches Nominal   |
| <b>Expansion Device:</b>    | Threaded Stem  |
| <b>Grip Length:</b>         | 0.250 Inches Nominal   |
| <b>Countersink Angle:</b>   | 125.0 Degrees Nominal  |
| <b>Material:</b>            | Aluminum Sleeve  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.