

**Description**

diameter: 5/32", grip range: 0.251" - 0.312", flush head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3214-5-5](#)

SKU / Model:	CR3214505
Minimum Qty (MOQ):	100
NSN:	5320-01-385-5461
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



## P/N CR3214-5-05 Specifications

<b>Fastener Length:</b>	0.410 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.158 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.232 Inches Nominal
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.370 Inches Nominal
<b>Countersink Angle:</b>	125.0 Degrees Nominal
<b>Material:</b>	Aluminum Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.