

Description

diameter: 5/32", grip range: 0.313" - 0.375", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3214-5-6](#)

SKU / Model:	CR3214506
Minimum Qty (MOQ):	100
NSN:	5320-01-476-4065
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N CR3214-5-06 Specifications

Fastener Length:	0.480 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.232 Inches Nominal
Expansion Device:	Threaded Stem
End Item Identification:	Sentry E3d
Grip Length:	0.375 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Ultimate Shear Strength 50,000 Psi; Maximum Temperature 250 Degrees F
Material:	Aluminum Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.