

## Description

diameter: 5/32", grip range: 0.065" - 0.125", flush head, 5056 aluminum sleeve, 8740 steel stem, CR3214 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CR3214-5-02](#)

SKU / Model:	CR321452
Minimum Qty (MOQ):	100
NSN:	5320-01-345-3796
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3214-5-2 Specifications

<b>Fastener Length:</b>	1.025 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.158 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.230 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.230 Inches Nominal
<b>Minimum Tensile Strength:</b>	530 Pounds Per Square Inch
<b>Shear Strength:</b>	1245 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Sleeve Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Sleeveams 6322 Assn Std 2nd Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleeve cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Sleeveqq-p-416,type II,class 2 Fed Spec 2nd Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.