

Description

Fastener Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3214-5-04](#)

| | |
|-------------------------|---|
| SKU / Model: | CR321454 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-385-5429 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N CR3214-5-4 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.359 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.158 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.237 Inches Nominal |
| Expansion Device: | Threaded Stem |
| Grip Length: | 0.310 Inches Nominal |
| Countersink Angle: | 125.0 Degrees Nominal |
| Material: | Aluminum Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.