

Description

Fastener Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3214-5-04](#)

SKU / Model:	CR321454
Minimum Qty (MOQ):	100
NSN:	5320-01-385-5429
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3214-5-4 Specifications

Fastener Length:	0.359 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.158 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.237 Inches Nominal
Expansion Device:	Threaded Stem
Grip Length:	0.310 Inches Nominal
Countersink Angle:	125.0 Degrees Nominal
Material:	Aluminum Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.