

Description

diameter: 3/16", grip range: 0.126" - 0.187", flush head, 5056 aluminum sleeve, 8740 steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3214-6-3](#)

SKU / Model:	CR3214603
Minimum Qty (MOQ):	100
NSN:	5320-01-500-0204
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3214-6-03 Specifications

Fastener Length:	0.325 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.225 Inches Minimum And 0.233 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
End Item Identification:	Aircraft, Thunderbolt li, A-10
Grip Length:	0.1875 Inches Nominal
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Collar
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Collar
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Collar
Surface Treatment Document And Classification:	Qq-p-416, Ty li, CI 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.