

**Description**

diameter: 3/16", grip range: 0.313" - 0.375", flush head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

**Alternate Part Numbers**

[CR3214-6-6](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3214606                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5320-01-515-5992                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

## P/N CR3214-6-06 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.482 Inches Minimum And 0.512 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.188 Inches Minimum And 0.192 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.295 Inches Minimum And 0.303 Inches Maximum                                  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>End Item Identification:</b>                       | A-10   |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>                                      | Iron Alloy 660 Collar  |
| <b>Material:</b>                                      | Steel Comp 8740 Stem   |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Stem                                |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Collar                              |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve                              |
| <b>Surface Treatment:</b>                             | Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment:</b>                             | Passivate Collar   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Collar                              |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Type Ii, Class 2 Fed Spec Single Treatment Response Stem              |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3214-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.