

Description

diameter: 1/8", grip range: 0.438" - 0.500", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3222-4-8](#)

SKU / Model:	CR3222408
Minimum Qty (MOQ):	100
NSN:	5320-01-150-8043
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N CR3222-4-08 Specifications

Fastener Length:	0.820 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.126 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.225 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-4-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.