

**Description**

Fastener Length: 1/2", CR3222 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3222-5-02](#)

SKU / Model:	CR322252
Minimum Qty (MOQ):	100
NSN:	5320-01-150-8044
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3222-5-2 Specifications

<b>Fastener Length:</b>	0.470 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.157 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.286 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.