

**Description**

Fastener Length: 1/2", CR3222 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR322253                                    |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-150-8045                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N CR3222-5-3 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.530 Inches Nominal   |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.157 Inches Nominal   |
| <b>Head Major Diameter:</b> | 0.286 Inches Nominal   |
| <b>Expansion Device:</b>    | Serrated Stem-type W   |
| <b>Grip Length:</b>         | 0.126 Inches Minimum And 0.187 Inches Maximum                                  |
| <b>Countersink Angle:</b>   | 100.0 Degrees Nominal  |
| <b>Material:</b>            | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>            | Steel Corrosion Resisting Locking Ring   |
| <b>Material:</b>            | Steel Corrosion Resisting Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.