

**Description**

diameter: 3/16", grip range: 0.126" - 0.187", flush head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3222-6-3](#)

SKU / Model:	CR3222603
Minimum Qty (MOQ):	100
NSN:	5320-01-150-8053
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N CR3222-6-03 Specifications

<b>Fastener Length:</b>	0.570 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.189 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.