

**Description**

diameter: 3/16", grip range: 0.313" - 0.375", flush head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3222-6-6](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CR3222606                                   |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-150-8056                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3222-6-06 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.760 Inches Nominal   |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.189 Inches Nominal   |
| <b>Shank Style:</b>         | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b> | 0.353 Inches Nominal   |
| <b>Expansion Device:</b>    | Serrated Stem-type W   |
| <b>Grip Length:</b>         | 0.313 Inches Minimum And 0.375 Inches Maximum                                  |
| <b>Countersink Angle:</b>   | 100.0 Degrees Nominal  |
| <b>Material:</b>            | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>            | Steel Corrosion Resisting Locking Ring   |
| <b>Material:</b>            | Steel Corrosion Resisting Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-6-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.