

Description

diameter: 3/16", grip range: 0.376" - 0.437", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3222-6-7](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3222607 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-150-8057 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CR3222-6-07 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.820 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.189 Inches Nominal |
| Head Major Diameter: | 0.353 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Corrosion Resisting Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3222-6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.