

Description

diameter: 1/8", grip range: 0.376" - 0.437", universal head, aluminum sleeve, corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3223-4-7](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3223407 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-463-9100 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N CR3223-4-07 Specifications

| | |
|---------------------------------|---|
| Fastener Length: | 0.537 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| End Item Identification: | Aircraft, Awacs, E-3a |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Stem |
| Surface Treatment: | Cadmium Stem Or Passivate Stem |
| Surface Treatment: | Chromate Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-4-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.