

Description

diameter: 5/32", grip range: 0.063" - 0.125", universal head, aluminum sleeve, corrosion resistant steel stem, CR3223 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3223-5-2](#)

SKU / Model:	CR3223502
Minimum Qty (MOQ):	100
NSN:	5320-01-287-7133
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR3223-5-02 Specifications

Fastener Length:	0.200 Inches Minimum And 0.230 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas9301 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.