

Description

diameter: 5/32", grip range: 0.313" - 0.375", universal head, aluminum sleeve, corrosion resistant steel stem, CR3223 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3223-5-6](#)

| | |
|-------------------------|---|
| SKU / Model: | CR3223506 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-289-0031 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N CR3223-5-06 Specifications

| | |
|---|--|
| Fastener Length: | 0.450 Inches Minimum And 0.480 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.156 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas9301 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-5-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.