

Description

diameter: 5/32", grip range: 0.376" - 0.437", universal head, aluminum sleeve, corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3223-5-7](#)

SKU / Model:

CR3223507

Minimum Qty (MOQ):

100

NSN:

5320-01-429-9971

ECCN:

EAR99



* See page 2 for technical characteristics

P/N CR3223-5-07 Specifications

Fastener Length:	0.543 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.438 Inches Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 632 Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-5-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.