

Description

diameter: 3/16", grip range: 0.063" - 0.125", universal head, aluminum sleeve, corrosion resistant steel stem, CR3223 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3223-6-2](#)

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | CR3223602 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-457-3705 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N CR3223-6-02 Specifications

| | |
|-----------------------------|-----------------------------------------------|
| Fastener Length: | 0.262 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.090 Inches Maximum |
| Shank Diameter: | 0.188 Inches Minimum And 0.192 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 632 Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-6-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.