

**Description**

diameter: 3/16", grip range: 0.126" - 0.187", universal head, aluminum sleeve, corrosion resistant steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3223-6-3](#)

SKU / Model:	CR3223603
Minimum Qty (MOQ):	100
NSN:	5320-01-289-0033
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR3223-6-03 Specifications

<b>Fastener Length:</b>	0.295 Inches Minimum And 0.325 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.188 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas9301 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-6-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.