

Description

diameter: 3/16", grip range: 0.501" - 0.562", universal head, aluminum sleeve, corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3223-6-9](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | CR3223609 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-204-1997 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N CR3223-6-09 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.670 Inches Minimum And 0.700 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.312 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 632 Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-6-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.