

Description

diameter: 3/16", grip range: 0.501" - 0.562", universal head, aluminum sleeve, corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3223-6-9](#)

SKU / Model:	CR3223609
Minimum Qty (MOQ):	100
NSN:	5320-01-204-1997
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR3223-6-09 Specifications

Fastener Length:	0.670 Inches Minimum And 0.700 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.312 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 632 Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3223-6-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.