

**Description**

diameter: 1/8", grip range: 0.313" - 0.375", flush head, aluminum sleeve, corrosion resistant steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3224-4-6](#)

SKU / Model:	CR3224406
Minimum Qty (MOQ):	100
NSN:	5320-01-164-8613
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N CR3224-4-06 Specifications

<b>Fastener Length:</b>	0.444 Inches Minimum And 0.474 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.129 Inches Maximum
<b>Head Major Diameter:</b>	0.196 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 632 Stem
<b>Material Document And Classification:</b>	Ams 5657 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3224-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.