

Description

diameter: 5/32", grip range: 0.188" - 0.250", flush head, aluminum sleeve, corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3224-5-4](#)

SKU / Model:	CR3224504
Minimum Qty (MOQ):	100
NSN:	5320-01-164-8616
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3224-5-04 Specifications

Fastener Length:	0.325 Inches Minimum And 0.355 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.247 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 632 Stem
Material Document And Classification:	Ams 5657 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Type 1 Class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3224-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.