

Description

diameter: 5/32", grip range: 0.376" - 0.437", nas1097, flush head, 5056 aluminum sleeve, 15-7 ph corrosion resistant steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | CR3224507 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-497-4871 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N CR3224-5-07 Specifications

| | |
|---|--|
| Fastener Length: | 0.543 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.243 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 632 Stem |
| Material Document And Classification: | Ams 5657 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Cadmium Stem Or Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Type I Cl. 2 Fed Spec Single Treatment Response Stem Or Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3224-5-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.