

Description

diameter: 5/32", grip range: 0.438" - 0.500", nas1097 spec, flush head, 5056 aluminum sleeve, 15-7 ph corrosion resistant steel stem, CR3224 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3224-5-8](#)

SKU / Model:	CR3224508
Minimum Qty (MOQ):	100
NSN:	5320-01-497-7891
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N CR3224-5-08 Specifications

Fastener Length:	0.605 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.239 Inches Minimum And 0.246 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.463 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 1100 Sleeve
Material:	Iron Alloy 660 Collar
Material:	Steel Comp 632 Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3224-5-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.