



Military-Fasteners.com

P/N CR3242-4-01

Description

diameter: 1/8", grip range: 0.045" - 0.062", flush head, locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3242-4-1](#)

SKU / Model:	CR3242401
Minimum Qty (MOQ):	100
NSN:	5320-01-422-7081
Schedule B:	7318.23.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CR3242-4-01 Specifications

Fastener Length:	0.200 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.140 Inches Minimum And 0.143 Inches Maximum
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.045 Inches Minimum And 0.062 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Collar
Material:	Steel Comp 8740 Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3242-4-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.