

P/N CR3242-4-03

Description

diameter: 1/8", grip range: 0.126" - 0.187", flush head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem, CherryMax, CR3242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3242-4-3 CR3242-04-03

SKU / Model:	CR3242403
Minimum Qty (MOQ):	100
NSN:	5320-01-034-1885
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets









P/N CR3242-4-03 Specifications

0.267 Inches Minimum And 0.287 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.140 Inches Minimum And 0.143 Inches Maximum
Self-plugging Mechanically Locked Stem
0.211 Inches Minimum
Serrated Stem-type W
0.126 Inches Minimum And 0.187 Inches Maximum
100.0 Degrees Nominal
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Body
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Body
Chromate Body
Cadmium Stem
Mil-c-5541 Mil Spec Single Treatment Response Body
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3242-4-03 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.