

Description

diameter: 1/8", grip range: 0.376" - 0.437", flush head, locked spindle, oversized diameter, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3242-4-7](#)

SKU / Model:	CR3242407
Minimum Qty (MOQ):	100
NSN:	5320-01-090-3166
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3242-4-07 Specifications

Fastener Length:	0.541 Inches Minimum And 0.561 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std 2nd Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-a-416,type 2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3242-4-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.