

P/N CR3242-4-4

Military-Fasteners.com

Description

Fastener Length: 3/8", CR3242 series rivet

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

Alternate Part Numbers

CR	32	42-4	4-0	4

SKU / Model:	CR324244
Minimum Qty (MOQ):	100
NSN:	5320-01-034-1883
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3242-4-4 Specifications

Fastener Length:	0.330 Inches Minimum And 0.350 Inches Maximum		
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)		
Shank Diameter:	0.140 Inches Minimum And 0.143 Inches Maximum		
Head Major Diameter:	0.211 Inches Minimum		
Expansion Device:	Serrated Stem-type W		
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum		
Countersink Angle:	100.0 Degrees Nominal		
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.		
Material:	Aluminum Alloy 5056 Body		
Material:	Steel Comp 8740 Stem		
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem		
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body		
Surface Treatment:	Chromate Body		
Surface Treatment:	Cadmium Stem		
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Body		
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem		

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3242-4-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.