

## P/N CR3242-5-02

## **Description**

diameter: 5/32", grip range: 0.063" - 0.125", flush head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem, CR3242 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

CR3242-5-2

SKU / Model:	CR3242502
Minimum Qty (MOQ):	100
NSN:	5320-01-034-6673
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N CR3242-5-02 Specifications

Fastener Length:	0.236 Inches Minimum And 0.256 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.173 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.270 Inches Minimum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Iroquois Uh-1; U-2 Support Equipment; Aircraft, Stratofortress B-52; Engine, Aircraft, Tf39-fe-1 (c-5a); Aircraft, Phantom F-4; Aircraft, Stratolifter C-135; T1a Aircraft; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p)
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Chromate Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3242-5-02">https://military-fasteners.com/rivets/blind+rivets/CR3242-5-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.