

# P/N CR3242-5-08

Military-Fasteners.com

#### Description

diameter: 5/32", grip range: 0.438" - 0.500", flush head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

<u>CR3242-5-8</u>	
SKU / Model:	CR3242508
Minimum Qty (MOQ):	100
NSN:	5320-01-159-9410
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



### P/N CR3242-5-08 Specifications

0.611 Inches Minimum And 0.631 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.172 Inches Minimum And 0.176 Inches Maximum
Self-plugging Mechanically Locked Stem
0.290 Inches Maximum
Serrated Stem-type W
0.438 Inches Minimum And 0.500 Inches Maximum
99.0 Degrees Minimum And 101.0 Degrees Maximum
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Sleeve
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Sleeve
Chromate Sleeve
Cadmium Stem And Chromate Stem
Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3242-5-08</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.