

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR3242511
Minimum Qty (MOQ):	100
NSN:	5320-01-497-7880
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3242-5-11 Specifications

Fastener Length:	0.809 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.6405 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 1100 Sleeve
Material:	Iron Alloy 660 Collar
Material:	Steel Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3242-5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.