

Description

Fastener Length: 1",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | CR3242610 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-150-2762 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3242-6-10 Specifications

| | |
|--|---|
| Fastener Length: | 1.010 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.201 Inches Nominal |
| Head Major Diameter: | 0.353 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.563 Inches Minimum And 0.625 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply. |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Corrosion Resisting Locking Ring |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams6322 Assn Std 3rd Material Response Stem |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Locking Ring |
| Material Document And Classification: | Qq-c-430 Fed Spec 2nd Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3242-6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.