



Military-Fasteners.com

P/N CR3242-6-11

Description

diameter: 3/16", grip range: 0.626" - 0.687", 100° , flush head - locked spindle - oversized diameter - 5056 aluminum sleeve - 8740 steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR3242611
Minimum Qty (MOQ):	100
NSN:	5320-01-150-2763
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3242-6-11 Specifications

Fastener Length:	1.070 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.201 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.353 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.626 Inches Minimum And 0.687 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Material Document And Classification:	Qq-c-430 Fed Spec 2nd Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3242-6-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.