

**Description**

Diameter: 1/8", grip range: 0.188" - 0.250", universal head, locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3243 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3243-4-4](#)

SKU / Model:	CR3243404
Minimum Qty (MOQ):	100
NSN:	5320-01-550-1068
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N CR3243-4-04 Specifications

<b>Fastener Length:</b>	0.242 Inches Minimum And 0.314 Inches Maximum
<b>Head Style:</b>	Countersunk W/protruding Stud
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Drive Pin
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Collar
<b>Material:</b>	Steel Comp 8740 Stem
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment:</b>	Passivate Collar

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.