



Military-Fasteners.com

P/N CR3243-4-04

Description

Diameter: 1/8", grip range: 0.188" - 0.250", universal head, locked spindle, oversized diameter, aluminum sleeve, steel stem, CR3243 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3243-4-4](#)

SKU / Model:	CR3243404
Minimum Qty (MOQ):	100
NSN:	5320-01-550-1068
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3243-4-04 Specifications

Fastener Length:	0.242 Inches Minimum And 0.314 Inches Maximum
Head Style:	Countersunk W/protruding Stud
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Drive Pin
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Corrosion Resisting Collar
Material:	Steel Comp 8740 Stem
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Collar

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.