

Description

diameter: 1/8", grip range: 0.313" - 0.375", universal head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem, CR3243 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3243-4-6](#)

SKU / Model:	CR3243406
Minimum Qty (MOQ):	100
NSN:	5320-01-040-4810
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3243-4-06 Specifications

Fastener Length:	0.455 Inches Minimum And 0.475 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.140 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Helicopter, Advance Attack, Ah-1w; Aircraft, Phantom F-4; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Aircraft, Delta Dart F-106; Aircraft, Stratofortress B-52; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Stratolifter C-135; Aircraft, F-111; Aircraft, Hercules C-130; Helicopter Observation (ahip), Oh-58d
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Surface Treatment:	Chromate Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.