

Description

diameter: 1/8", grip range: 0.376" - 0.437", universal head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem, CR3243 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3243-4-7](#)

SKU / Model:	CR3243407
Minimum Qty (MOQ):	100
NSN:	5320-01-091-1864
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N CR3243-4-07 Specifications

<b>Fastener Length:</b>	0.541 Inches Minimum And 0.561 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Wsd: Helicopter, Super Jolly H-53; Aircraft, B-1b; Aircraft, Hercules C-130; Aircraft, Harrier Av-8b; Aircraft, Eagle F-15; Aircraft, Galaxy C-5; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Helicopter, Cobra/attack, Ah-1j; Helicopter Observation (ahip), Oh-58d
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Criticality Code Justification:</b>	Feat
<b>Special Features:</b>	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply; Weapon System Essential See Agavgwsd
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams6322 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-4-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.