

**Description**

diameter: 1/8", grip range: 0.501" - 0.562", universal head - locked spindle - oversized diameter - 5056 aluminum sleeve - 8740 steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3243-4-9](#)

SKU / Model:	CR3243409
Minimum Qty (MOQ):	100
NSN:	5320-01-094-4411
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N CR3243-4-09 Specifications

<b>Fastener Length:</b>	0.666 Inches Minimum And 0.686 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Wsd: Aircraft, Galaxy C-5; Helicopter Observation (ahip), Oh-58d; Aircraft, Eagle F-15; Aircraft; Harrier Av-8b
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Criticality Code Justification:</b>	Feat
<b>Special Features:</b>	Weapon System Essential
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams6322 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2,class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-4-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.