

P/N CR3243-4-7

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3243-4-07

<u>CR32.13 1 07</u>	
SKU / Model:	CR324347
Minimum Qty (MOQ):	100
NSN:	5320-01-091-1864
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N CR3243-4-7 Specifications

0.541 Inches Minimum And 0.561 Inches Maximum
Universal
0.054 Inches Minimum And 0.064 Inches Maximum
0.139 Inches Minimum And 0.143 Inches Maximum
Self-plugging Mechanically Locked Stem
0.240 Inches Minimum And 0.260 Inches Maximum
Serrated Stem-type W
Wsd: Helicopter, Super Jolly H-53; Aircraft, B-1b; Aircraft, Hercules C-130; Aircraft, Harrier Av-8b; Aircraft, Eagle F-15; Aircraft, Galaxy C-5; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Helicopter, Cobra/attack, Ah-1j; Helicopter Observation (ahip), Oh-58d
0.376 Inches Minimum And 0.437 Inches Maximum
Feat
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply; Weapon System Essential See Agavgwsd
Aluminum Alloy 5056 Sleeve
Steel Comp 8740 Stem
Ams6322 Assn Std 2nd Material Response Stem
Qq-a-430 Fed Spec 1st Material Response Sleeve
Cadmium Stem
Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3243-4-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.