

Description

diameter: 5/32", grip range: 0.025" - 0.062", universal head, locked spindle, oversized diameter, 5056 aluminum sleeve, 8740 steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3243-5-1](#)

SKU / Model:	CR3243501
Minimum Qty (MOQ):	100
NSN:	5320-01-091-9175
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3243-5-01 Specifications

Fastener Length:	0.193 Inches Minimum And 0.213 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	W/s: Aircraft, Stratolifter C-135; Aircraft, Eagle F-15; Aircraft, Phantom F-4, Helicopter, Seahawk, H-60; Helicopter, Electronic Countermeasures, Eh-60a; Aircraft, Thunderbolt II, A-10; Aircraft, Galaxy C-5; Helicopter, Super Jolly H-53; Aircraft, Starlifter C-141
Grip Length:	0.062 Inches Maximum
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-5-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.