

**Description**

diameter: 5/32", grip range: 0.188" - 0.250", universal head, locked spindle, oversized diameter, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3243-5-4](#)

SKU / Model:

CR3243504

Minimum Qty (MOQ):

100

NSN:

5320-01-550-1070

ECCN:

EAR99



\* See page 2 for technical characteristics

## P/N CR3243-5-04 Specifications

<b>Fastener Length:</b>	0.242 Inches Minimum And 0.314 Inches Maximum
<b>Head Style:</b>	Countersunk W/protruding Stud
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Drive Pin
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Corrosion Resisting Collar
<b>Material:</b>	Steel Comp 8740 Stem
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment:</b>	Passivate Collar

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-5-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.