

**Description**

diameter: 5/32", grip range: 0.501" - 0.562", universal head, locked spindle, oversized, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3243-5-9](#)

SKU / Model:	CR3243509
Minimum Qty (MOQ):	100
NSN:	5320-01-092-8759
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N CR3243-5-09 Specifications

<b>Fastener Length:</b>	0.674 Inches Minimum And 0.694 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.324 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams6322 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-5-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.