

Description

diameter: 5/32", grip range: 0.501" - 0.562", universal head, locked spindle, oversized, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR3243-5-9](#)

| | |
|--------------------|------------------|
| SKU / Model: | CR3243509 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-092-8759 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CR3243-5-09 Specifications

| | |
|---|--|
| Fastener Length: | 0.674 Inches Minimum And 0.694 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.172 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.302 Inches Minimum And 0.324 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.501 Inches Minimum And 0.562 Inches Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams6322 Assn Std 2nd Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec 1st Material Response Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Type2,class 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3243-5-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.